





CE42LH2R





- Fully-approved oil-, smoke- and dust-protection
- IP40 foreign bodies protection
- Screen size 105 cm (42 inch)
- Full HD resolution (1,920 x 1,080) in 16: 9 aspect ratio
- Contrast ratio: 1,100 : 1, brightness: 500 cd/m²
- Suitable for industrial installations, point of sales, sporting events, restaurants, pubs and much more
- Acrylic screen surface with vandalism protection
- Anti-corrosive anodized aluminium cabinet
- Network integration (optional) for maintaining and controlling the monitor on the LAN
- 3 years warranty





CE42LH2R

| TECHNICAL DATA | CE42LH2R |
|------------------------------|---|
| Category | Professional LCD monitor |
| Type | Liquid Crystal Display Panel * |
| IP Rating | IP40 foreign bodies protection |
| Screen size (diagonal image) | 42' (105 cm) |
| Active Screen Area (W x H) | 93.0 x 52.3 cm |
| Aspect Ratio | 16.9 |
| Resolution in pixels | 1,920 × 1,080 (HDTV 1,080p) |
| Pixel pitch | 0.4845 x 0.4845 mm |
| Brightness | 500 cd/m ² |
| Contrast Ratio | 1000:1 |
| Viewing Angle | 178° (horizontal and vertical) |
| Response time | 9 ms (gray to gray) |
| Grev scale value | 8 bit |
| Number of colors | 16.7 Mio |
| Color systems | PAL, NTSC3.58 (AV in), SECAM |
| Computer compatibility | U-XGA, W-XGA, S-XGA, XGA, S-VGA, VGA, 1,080i |
| Input Terminals | D-Sub15 5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr) Component (Y, Pb, Pr) BNC (Video) Scart (RGB) Video D-Sub9 (RS232) 2 x RCA (R/L mono) for audio |
| Output Terminals | DVI-D (digital/HDCP) 3.5 mm stereo jack for audio 5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr) Component (Y, Pb, Pr) BNC (Video) D-Sub9 (RS232) 2 x RCA (R/L mono) for audio External speaker output (2 x 6 W) |
| Operating Temperature | 0 °C - 40 °C |
| Storage Temperature | -20 °C - 60 °C |
| Depth of front glass | 4 mm |
| Mechanical strength | 91 N/mm² |
| Voltage | 100 - 240 V (50 - 60 Hz) |
| Power Consumption | 210 W/0.8 W (stand-by mode) |
| Dimensions (W x H x D) | 1027 x 624 x 178 mm |
| Weight | 33 kg |
| Vesa Mounting Sizes | 200 x 200 mm |
| Color of cabinet | Silver |
| Warranty | 3 years, 24-hr replacement service (D/CH/I/F - except overseas) |
| Standard accessories | user manual, remote control, batteries, power cable |
| Optional Accessories | LD Net Organizer Plus (POA-LN02) |
| Special feature | protection against oil, smoke and dust, anodized aluminium case, acrylic screen surface with vandalism protection, portrait and landscape mode, extensive input & output terminals |

^{*} IP = Protection class





Technical specifications subject to change without notice. Date 03/2010

