



CE52LH2R



**FULL
HD
1080p**

- Fully-approved oil-, smoke- and dust-protection
- IP40 foreign bodies protection
- Screen size 132 cm (52 inch)
- Full HD resolution (1,920 x 1,080) in 16 : 9 aspect ratio
- Contrast ratio: 2,000 : 1, brightness: 700 cd/m²
- Acrylic screen surface with vandalism protection
- Anti-corrosive anodized aluminium cabinet
- Suitable for industrial installations, point of sales, sporting events, restaurants, pubs and much more
- Network integration (optional) for maintaining and controlling the monitor on the LAN
- 3 years warranty

CE52LH2R

TECHNICAL DATA	CE52LH2R
Category	Professional LCD monitor
Type	Liquid Crystal Display Panel *
IP Rating	IP40 foreign bodies protection
Active Screen Area (W x H)	115.2 x 64.8 cm
Aspect Ratio	16:9
Resolution in pixels	1,920 x 1,080 (HDTV 1,080p)
Pixel pitch	0.6 x 0.6 mm
Brightness	700 cd/m ²
Contrast Ratio	2000 : 1
Viewing Angle	176° (horizontal and vertical)
Response time	8 ms (gray to gray)
Grey scale value	8 bit
Number of colors	16.7 Mio
Color systems	PAL, NTSC3.58 (AV in), SECAM
Computer compatibility	U-XGA, W-XGA, S-XGA, XGA, S-VGA, VGA, 1,080i
Input Terminals	D-Sub15 5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr) Component (Y, Pb, Pr) BNC (Video) Scart (RGB) Video D-Sub9 (RS232) 2 x RCA (R/L mono) for audio DVI-D (digital/HDCP) 3.5 mm stereo jack for audio
Output Terminals	5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr) Component (Y, Pb, Pr) BNC (Video) D-Sub9 (RS232) 2 x RCA (R/L mono) for audio External speaker output (2 x 8 W)
Operating Temperature	0 °C - 40 °C
Storage Temperature	-20 °C - 60 °C
Depth of front glass	6 mm
Mechanical strength	91 N/mm ²
Voltage	100 - 240 V (50 - 60 Hz)
Power Consumption	360 W/0.8 W (stand-by mode)
Dimensions (W x H x D)	1304 x 804 x 227 mm
Weight	65 kg
Vesa Mounting Sizes	420 x 516 mm , 997 x 420 mm
Color of cabinet	Silver
Warranty	3 years, 24-hr replacement service (D/CH/I/F - except overseas)
Standard accessories	user manual, remote control, batteries, power cable
Optional Accessories	LD Net Organizer Plus (POA-LN02) , Wall mount (POA-WM52H), Wall mount (POA-WM52V)
Special feature	protection against oil, smoke and dust, anodized aluminium case, acrylic screen surface with vandalism protection, portrait and landscape mode, picture-in-picture and picture-by-picture function, extensive input & output terminals

* IP = Protection class



Technical specifications subject to change without notice. Date 03/2010

