



RC-2C

Wall Plate – RS-232 & IR Controller



The **RC-2C** is a 2-button controller that sends a series of RS-232 or IR commands with the push of a button. It operates serial or IR-controlled devices such as projectors, displays, and switchers.



RC-2C

FEATURES

- **2 Multi-Color & Label Capable Buttons.**
- **1 RS-232 Port** - Controls a device via serial control protocols.
- **1 IR Port** - Controls a device via IR protocols.
- **Optional Ports** - Add control ports with the PL-18 Control Port Expander.
- **Memory** - Up to 4 commands per macro and 4 toggling macros per button.
- **Dimensions** - 7.9cm x 1.59cm x 12.4cm (3.12" x 0.63" x 4.88") US; 8.6cm x 1.59cm x 8.6cm (3.39" x 0.63" x 3.39") and 8cm x 1.59cm x 8cm (3.15" x 0.63" x 3.15") EU W, D, H.
- **Wall Plate Size** - 1 gang EU/US.

TECHNICAL SPECIFICATIONS

- PORTS:** 1 RS-232 on a terminal block connector; IR OUT on a terminal block connector.
- POWER SOURCE:** 12V DC, 40mA.
- DIMENSIONS:** 7.9cm x 1.59cm x 12.4cm (3.12" x 0.63" x 4.88") US; 8.6cm x 1.59cm x 8.6cm (3.39" x 0.63" x 3.39") and 8cm x 1.59cm x 8cm (3.15" x 0.63" x 3.15") EU W, D, H.
- WEIGHT:** 0.3kg (0.67lbs) approx.
- ACCESSORIES:** Kramer's Windows®-based configuration software, power supply.
- OPTIONS:** RS-232 9-pin D-sub port to 3-pin terminal block connector cable (C-D9F/3PM-0.6).