













Ultra-portable presentations with no PC

Do you ever get tired of carrying a laptop into every meeting? Do you wish you could cut down on cables & setup time; getting straight to business? Let the ML500 set you free with its extensive built-in multimedia players. Alternatively connect & display images from your laptop, netbook, iPad2[®] or tablet PC for ultimate flexibility.*

Using the latest "Lamp-free" LED technology for exceptional colour fidelity, reliability and longevity, the Optoma ML500 ultra-slim portable projector is your perfect business partner. In many situations the perceived brightness of an LED projector can be up to twice the brightness of an equivalent lamp-based projector; when combined with the extraordinary life of LEDs, you can be sure that your presentations will be clear and bright for many years to come.

ON-BOARD MULTIMEDIA PLAYERS

View photos, videos, Microsoft Office & Adobe PDF files directly from the on-board memory, an SD card or a USB memory stick – without the need to convert them. Add music to your slideshow or presentation for that extra polish.

Presentation & Documents

With native support for Microsoft Office and Adobe PDF files, you can simply save your work onto the ML500 internal memory, an SD card* or USB memory stick* and you are ready to go. Effortlessly pan, zoom and flick between multiple pages using the supplied slim-line remote for that seamless, professional presentation.



Photos

Insert the SD card straight from your camera to instantly share ideas, on location with small or large groups, without the need for extra cables. Alternatively leave a slideshow with audio running in the background before kicking off your meeting, to whet their appetite and stimulate discussion.



*SD Card & USB memory stick not included. Connection to some devices may require additional cables, available separately.

Videos

Sit back after a long day to enjoy your favourite movies... without the need for file conversion; the ML500 directly supports all the most popular video & music file formats and being both HD-Ready and LED, you can also be sure of vibrant colours, depth and clarity that will not disappoint.



GREAT CONNECTIVITY

Equipped with HDMI, VGA, Video & Audio Inputs, you can easily connect your iPad2[®], Laptop, DVD player or tablet PC. With so many options you are spoilt for choice.



USB Display



What if your netbook or tablet has no video output? With USB-Display you can now mirror your desktop to the projector using the supplied mini-USB cable, for ultimate flexibility.

EFFORTLESS PRESENTING...ON THE MOVE

Designed with convenience in mind, the ML500 makes setting up hassle free, just plug-in, switch on and you are away...

Project anywhere, even without a screen! Advanced wall colour compensation automatically adjusts the on screen image to maintain perfect colour balance wherever you are.

Create a 60" (1.5m) image from only 6'(1.8m) away; making a big impact...even in smaller rooms.



Tilt the projector up to 40° and the image will automatically re-adjust, without you lifting a finger – just point and present.



A luxury carry-case is provided enabling you to take the ML500 anywhere, anytime.





We know that improving our products is the best way to reduce our impact on the environment. That's why at Optoma, we design our products to have a long usable life, use fewer materials, ship with the minimum packaging and be free of all possible toxic substances. Naturally, energy efficiency and being recyclable are built in at the design stage. With each new product, we strive towards minimising our environmental impact. For full details of Optoma Project Green please visit our website.

LED...THE FUTURE OF PROJECTION IS HERE!

Long life

As is typical with all lamp based projectors, image brightness will decrease over time until frequently, the costly lamp needs to be replaced. The ML500 uses cutting edge LED technology, with an exceptional life-span to completely eliminate the need for expensive replacement lamps. Saving you both time and money; while leaving you certain that your projector will be fully operational for many years to come.



High Brightness

Due to the exceptional colour fidelity created by LED technology; in many situations the perceived brightness of an LED projector can be up to twice the brightness of an equivalent lamp-based projector.



3D-READY

Using the inherent speed of DLP® technology, Optoma 3D Ready projectors can output video and images at an astonishing rate of 120Hz, allowing you to show full screen, full colour, stereoscopic 3D.



Design a city and walkthrough the streets; explore the world, travel through space, see inside the body; inspire your imagination and bring new ideas to life!

Useful for both professionals and educators alike, the ML500 brings both teaching and design to a whole new level of immersion and excitement.

5

8

ML500 SPECIFICATIONS

Native Resolution	WXGA 1280 x 800				
Brightness ¹	500 ANSI Lumens (LED)				
Contrast	3000:1				
Noise Level	29dB				
LED Life ²	20,000 hours				
Projections Lens	F/1.5, f=13.92mm, Fixed				
Throw Ratio	1.4:1 (Projection Distance:Image Width)				
Projection Distance	0.5 - 5.5m				
Image Size	0.43 - 4.57m (17" - 180") Diagonal 16:10				
Display Technology	Single 0.45" WXGA DMD chip DLP® Technology				
,	by Texas Instruments				
Weight / Dimensions (W x D x H)	1.14 kg / 220 x 170 x 43mm				
Remote Control	Full function remote with, multimedia control and direct				
	source selecting				
INPUTS	HDMI connector (Audio supported)				
	15 Pin D-Sub VGA Component via adaptor				
	S-Video 4 Pin Mini Din				
	Composite RCA				
	SD Card slot (for mutimedia) USB-A (for mutimedia) mini-USB (for USB Display & data transfer) Audio IN - 3.5mm jack				
Audio	2W Speaker				
Aspect Ratio	16:10 Native, 4:3 & 16:9 Compatible				
Auto Image Adjust	± 40 Degrees Vertical				
On Screen Display	13 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish,				
	Greek, Turkish				
Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p				
Multimedia Compatibility	Document - Microsoft PowerPoint [®] (ppt, pptx), Word [®]				
	(doc, docx), Excel [®] (xls, xlsx), Adobe (pdf)				
	Video - avi, mov, mp4, 3gp, ts, wmv, mkv, rm Photo - Jpeg, bmp				
	Music - mp3, acc, wma, ogg, wav				
Uniformity	80%				
Displayable Colours	1.07 billion				
Diopiayanio ovidula	1.07 billion				
Horizontal Scan Rate	1.07 billion 49.64kHz				
Horizontal Scan Rate	49.64kHz				
Horizontal Scan Rate Vertical Scan Rate	49.64kHz 50 – 120Hz				
Horizontal Scan Rate Vertical Scan Rate Power Supply	49.64kHz 50 – 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W Operating: 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max)				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security	49.64kHz 50 – 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W 0perating: 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Kensington [™] Lock Port				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions	49.64kHz 50 – 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W Operating: 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max)				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security	49.64kHz 50 – 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W 0perating: 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Kensington [™] Lock Port				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security	49.64kHz 50 – 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W Operating: 5 - 35 [°] C, 85% Humidity (Max), 2500m Attitude (Max) Kensington [™] Lock Port AC Power Cord, VGA Cable, mini-USB Cable, Carry Bag,				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security	49.64kHz 50 – 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W Operating: 5 - 35 [°] C, 85% Humidity (Max), 2500m Altitude (Max) Kensington [™] Lock Port AC Power Cord, VGA Cable, mini-USB Cable, Carry Bag, Full Function Card Remote (Inc.Battery), Quick Start				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories	49.64kHz 50 – 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories RoHS	49.64kHz 50 – 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W Operating: 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Kensington [™] Lock Port AC Power Cord, VGA Cable, mini-USB Cable, Carry Bag, Full Function Card Remote (Inc.Battery), Quick Start Guide, Warranty Card Compliant				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories RoHS	49.64kHz 50 – 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W 0perating: 5 - 35°C, 85% Humidity (Max), 2500m Atitude (Max) Kensington [™] Lock Port AC Power Cord, VGA Cable, mini-USB Cable, Carry Bag, Full Function Card Remote (Inc.Battery), Quick Start Guide, Warranty Card Compliant Warranty may vary by country. Please see				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories RoHS Warranty	49.64kHz 50 – 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W Operating: 5 - 35 [°] C, 85% Humidity (Max), 2500m Atitude (Max) Kensington [™] Lock Port AC Power Cord, VGA Cable, mini-USB Cable, Carry Bag, Full Function Card Remote (Inc.Battery), Quick Start Guide, Warranty Card Compliant Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories RoHS Warranty	49.64kHz 50 - 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories RoHS Warranty 3D Support	49.64kHz 50 – 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W Operating: 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Kensington [™] Lock Port AC Power Cord, VGA Cable, mini-USB Cable, Carry Bag, Full Function Card Remote (Inc.Battery), Quick Start Guide, Warranty Card Compliant Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details 800x600@120Hz - frame sequential 1024x768@120Hz - frame sequential				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories RoHS Warranty 3D Support	49.64kHz 50 - 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories RoHS Warranty 3D Support 3D Viewing	49.64kHz 50 – 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W Operating: 5 - 35°C, 85% Humidity (Max), 2500m Altitude (Max) Kensington™ Lock Port AC Power Cord, VGA Cable, mini-USB Cable, Carry Bag, Full Function Card Remote (Inc.Battery), Quick Start Guide, Warranty Card Compliant Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details 800x600@120Hz - frame sequential 1024x768@120Hz - frame sequential 1024x768@120Hz - frame sequential Requires Optoma DLP [®] Link [™] active shutter glasses – sold separately				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories RoHS Warranty 3D Support 3D Viewing	49.64kHz 50 - 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories RoHS Warranty 3D Support 3D Viewing	49.64kHz 50 - 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories RoHS Warranty 3D Support 3D Viewing	49.64kHz 50 - 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories RoHS Warranty 3D Support 3D Viewing	49.64kHz 50 - 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W				
Horizontal Scan Rate Vertical Scan Rate Power Supply Power Consumption Operating Conditions Security Standard Accessories RoHS Warranty 3D Support 3D Viewing	49.64kHz 50 - 120Hz 100 - 240V, 50 - 60Hz 120W Maximum, Standby Mode <1W				

EASY TO USE REMOTE CONTROL

ML500 Remote Control

- 1 Power
- 2 AV Mute3 Menu
- 3 Menu4 Display M
- 4 Display Mode5 Menu Navigation
- 6 Aspect Ratio
- 7 Volume Control
- 8 Direct source selection

ML500 Connections

- 9 SD Card Slot (up to 32GB)
- 10 USB-A (multimedia)
- 11 HDMI (Audio supported)
- 12 VGA (Component via adapter)
- 13 S-Video
- 14 Composite Video
- 15 Audio In
- 16 Mini-USB (Display & Data transfer)
- 17 Kensington[™] Lock

Exceptional Connectivity / Multiple Terminals



6

Projection Distance 0.5 - 5.5m WXGA (16:10 Aspect Ratio)						
Projection Distance (m)	Max. Horizontal Image Size (m)	Vertical Image Size (m)	Max Diagonal Image Size (m)	Max Diagonal Image Size (inch)	Max. Image Offset (m)	
0.50 1.50 2.50 3.50 4.50 5.50	0.36 1.07 1.79 2.50 3.21 3.93	0.22 0.67 1.12 1.56 2.01 2.46	0.42 1.26 2.11 2.95 3.79 4.63	16.58 49.74 82.91 116.07 149.23 182.39	0.01 0.03 0.06 0.08 0.10 0.12	

For guide purposes only

When projecting a 16:9/4:3 image the image sizes, screen width, height and offset information will differ from the above.



Optoma Europe Ltd. 42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ

www.optoma.eu

¹Brightness will vary depending on selected projector mode, environmental conditions and usage. ²Typical LED life achieved through testing. Will vary according to operational use and environmental conditions. Copyright © 2011, Optoma Europe Ltd. Microsoft PowerPoint[®], Excel[®], and Word[®], are registered trademarks of Microsoft Corporation. iPad[®] is a registered trademarks of Apple Inc. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP[®], BrilliantColor[™] and the DLP logo are registered trademarks of Texas Instruments. Some images may be simulated.